

## Roulement conique 47487R-47423-JTEKT - 47487R-47423-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/47487r-47423-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
69.850	120.650	32.545	32.545	26.195	3.6	0.8	150	218	3 100	4 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
47487R	47423	26.6	84.0	78.0	109.0	114.0	3.6	0.8	0.36	1.67	0.92	1.01	0.513

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428826
Diam. intérieur	69.85 mm
Diam. intérieur	2 3/4" inch
Diam. extérieur	120.65 mm
Diam. extérieur	4 3/4" inch
Epaisseur	32.545 mm
Epaisseur	1.281" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE