

## Roulement conique 567A-563-JTEKT - 567A-563-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/567a-563-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_a$ max.	$r_b$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
71.438	127.000	36.512	36.170	28.575	3.6	3.2	156	226	3 000	4 000

  

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)					Constant $e$	Axial load factors		(Refer to)		
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.		$r_b$ max.	$Y_1$	$Y_2$	Inner ring	Outer ring
567A	563	28.6	86.0	80.0	112.0	120.0	3.6	3.2	0.36	1.65	0.91	1.19	0.648

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428901
Diam. intérieur	71.438 mm
Diam. extérieur	127 mm
Épaisseur	36.512 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE