

Roulement conique 575SR-572-JTEKT - 575SR-572-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/575sr-572-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|---------|--------|--------|--------|------------------|------------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r_{max} | r_{min} | C_r | C_{10} | Grease lub. | Oil lub. |
| 76.200 | 139.992 | 36.512 | 36.098 | 28.575 | 6.7 | 3.2 | 175 | 262 | 2 700 | 3 600 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant e | Axial load factors | | (Refer) | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|------------|------------|--------------|--------------------|-------|------------|------------|
| Inner ring | Outer ring | | d_a | d_b | D_a | D_b | r_a max. | r_b max. | | Y_1 | Y_2 | Inner ring | Outer ring |
| 575SR | 572 | 31.0 | 99.0 | 86.0 | 125.0 | 133.0 | 6.7 | 3.2 | 0.40 | 1.49 | 0.82 | 1.61 | 0.779 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952429144 |
| Diam. intérieur | 76.2 mm |
| Diam. extérieur | 139.992 mm |
| Épaisseur | 36.512 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE