


## Roulement conique 661-653-JTEKT - 661-653-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/661-653-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_{\text{max}}$	$r_{\text{min}}$	$C_r$	$C_{10}$	Grease lub.	Oil lub.
79.375	146.050	41.275	41.275	31.750	3.6	3.2	208	301	2 600	3 400

Bearing No.		Load center (mm) $a$	Mounting dimensions (mm)						Constant $e$	Axial load factors		(Refer to) Mass (kg)	
Inner ring	Outer ring		$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.		$Y_1$	$Y_2$	Inner ring	Outer ring
661	653	33.4	96.0	90.0	131.0	139.0	3.6	3.2	0.41	1.47	0.61	2.04	0.880

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429250
Diam. intérieur	79.375 mm
Diam. extérieur	146.05 mm
Épaisseur	41.275 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE