

Roulement conique 749SR-742-JTEKT - 749SR-742-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/749sr-742-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
85.026	150.089	44.450	46.672	36.512	5.2	3.2	264	368	2 500	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
749SR	742	32.4	104.0	95.0	134.0	142.0	5.2	3.2	0.33	1.84	1.01	2.08	1.06

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429502
Diam. intérieur	85.026 mm
Diam. extérieur	150.089 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE