

Roulement conique 677-672-JTEKT - 677-672-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/677-672-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
85.725	168.275	41.275	41.275	30.162	3.6	3.2	224	349	2 200	3 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer to)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
677	672	38.6	105.0	99.0	149.0	160.0	3.6	3.2	0.47	1.28	0.70	2.89	1.22

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429564
Diam. intérieur	85.725 mm
Diam. extérieur	168.275 mm
Épaisseur	41.275 mm
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE