

## Roulement conique 787-772-JTEKT - 787-772-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/787-772-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_{\text{max}}$	$r_{\text{min}}$	$C_r$	$C_{10}$	Grease lub.	Oil lub.
104.775	180.975	47.625	48.006	38.100	7.1	3.2	288	438	2 100	2 800

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
787	772	39.5	129.0	116.0	161.0	168.0	7.1	3.2	0.39	1.56	0.86	2.87	1.92

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430034
Diam. intérieur	104.775 mm
Diam. extérieur	180.975 mm
Épaisseur	47.625 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE