

Roulement conique L521949R-L521910-JTEKT - L521949R-L521910-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/l521949r-l521910-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> _{1 min.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 107.950 | 146.050 | 21.432 | 21.432 | 16.670 | 1.6 | 1.6 | 86.4 | 167 | 2 300 | 3 100 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|--------------------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| L521949R | L521910 | 26.2 | 116.0 | 114.0 | 136.0 | 141.0 | 1.6 | 1.6 | 0.39 | 1.53 | 0.84 | 0.665 | 0.325 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952430065 |
| Diam. intérieur | 107.95 mm |
| Diam. extérieur | 146.05 mm |
| Épaisseur | 21.432 mm |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE