

Roulement conique 64450R-64700-JTEKT - 64450R-64700-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/64450r-64700-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> _{10v}	Grease lub.	Oil lub.
114.300	177.800	41.275	41.275	30.162	3.6	3.2	234	380	2 000	2 700

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
64450R	64700	42.8	131.0	125.0	160.0	172.0	3.6	3.2	0.52	1.16	0.64	2.45	1.10

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430270
Diam. intérieur	114.3 mm
Diam. extérieur	177.8 mm
Épaisseur	41.275 mm
Poids	3550 g
Conditionnement	1
Norme	Sans norme

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE