


## Roulement conique

### LM245846-LM245810-JTEKT - LM245846-LM245810-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/lm245846-lm245810-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_{a \max}$	$r_{b \max}$	$C_r$	$C_{10}$	Grease lub.	Oil lub.
230.188	317.500	47.625	52.388	36.513	3.2	3.2	488	928	970	1 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a \max.$	$r_b \max.$	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
LM245846	LM245810	50.5	242.0	238.0	309.0	312.0	3.2	3.2	0.33	1.80	0.99	8.25	2.78

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952431819
Diam. intérieur	230.188 mm
Diam. extérieur	317.5 mm
Épaisseur	47.625 mm
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE