


## Roulement conique

### LM245848-LM245810-JTEKT - LM245848-LM245810-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/lm245848-lm245810-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
231.775	317.500	47.625	52.388	36.513	3.2	3.2	488	928	970	1 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
LM245848	LM245810	50.5	244.0	240.0	308.0	312.0	3.2	3.2	0.33	1.80	0.99	8.02	2.78

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952431826
Diam. intérieur	231.775 mm
Diam. intérieur	9 1/8" inch
Diam. extérieur	317.5 mm
Diam. extérieur	12 1/2" inch
Epaisseur	47.625 mm
Epaisseur	1 7/8" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE