

## Roulement conique M249734-M249710-JTEKT - M249734-M249710-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/conique/m249734-m249710-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
231.775	358.775	71.438	71.438	53.975	6.4	3.2	773	1 590	920	1 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
M249734	M249710	64.4	258.0	253.0	335.0	343.0	6.4	3.2	0.33	1.80	0.99	19.9	6.44

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952431857
Diam. intérieur	231.775 mm
Diam. intérieur	9 1/8" inch
Diam. extérieur	358.775 mm
Diam. extérieur	14 1/8" inch
Epaisseur	71.438 mm
Epaisseur	2 13/16" inch
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE