

## Roulement à aiguilles BHTM810-JTEKT - BHTM810-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bhtm810-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>		
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Caged type		
								With open ends	With closed end
8	15	10	8.4	4.00	3.30	34 000	BHTM810		

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	7.991	8.000	14.977	14.995	6.5	7.3

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952469348
Diam. intérieur	8 mm
Diam. intérieur	0.315" inch
Diam. extérieur	15 mm
Diam. extérieur	0.591" inch
Epaisseur	10 mm
Epaisseur	0.394" inch
Poids	6.5 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE