

Roulement à aiguilles BHTM1612-JTEKT - BHTM1612-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bhtm1612-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | Oil lub. | Caged type With open ends With closed end |
| 16 | 24 | 12 | — | 8.00 | 8.45 | 21 000 BHTM1612 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 15.989 | 16.000 | 23.972 | 23.993 | 15 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470351 |
| Diam. intérieur | 16 mm |
| Diam. extérieur | 24 mm |
| Épaisseur | 12 mm |
| Poids | 15 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE