

Roulement à aiguilles 22BM2812-JTEKT - 22BM2812-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/22bm2812-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BH-M

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|----------|--------------------------------------|-------|---------------------------|-----------------|
| F_w | D | C | C_0 | C_{10} | Oil lub. | | Caged type | |
| | | | min. | | | | With open ends | With closed end |
| 22 | 28 | 12 | 9.6 | 11.6 | 22.9 | 5 800 | | |

| | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | | | |
|-----------------|-----------------------------|-----------------|------------------------|--------|-------------------|-----------------|----|----|
| | Full complement type | | Housing bore dia. (N7) | | With open ends | With closed end | | |
| | With open ends | With closed end | Shaft dia. (h6) min. | max. | min. | max. | | |
| 22BM2812 | | | 21.987 | 22.000 | 27.972 | 27.993 | 16 | 18 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952471051 |
| Diam. intérieur | 22 mm |
| Diam. extérieur | 28 mm |
| Épaisseur | 12 mm |
| Poids | 16 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE