

## Roulement à aiguilles 22MKM2812-JTEKT - 22MKM2812-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/22mkm2812-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{10}$	Oil lub.	Caged type With open ends    With closed end
22	28	12	9.3	9.10	13.5	16 000	<b>22MKM2812</b>

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φG) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	14	16

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471082
Diam. intérieur	22 mm
Diam. extérieur	28 mm
Épaisseur	12 mm
Poids	16 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE