

Roulement à aiguilles 22MKM2820-JTEKT - 22MKM2820-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/22mkm2820-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.	Caged type With open ends	With closed end
22	28	20	17.3	14.9	26.5	17 000		22MKM2820

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	27.972	27.993	25	28

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471167
Diam. intérieur	22 mm
Diam. extérieur	28 mm
Épaisseur	20 mm
Poids	28 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE