


## Roulement à aiguilles MKM2512-JTEKT - MKM2512-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/mkm2512-jtekt>

Drawn cup needle roller bearings ————— Koyo



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
F <sub>w</sub>	D	C	b min.	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.
25	32	12	9.3	9.05	12.4	14 000
						Caged type
						With open ends
						With closed end
						<b>MKM2512</b>

Full complement type		Recommended dimensions (mm)		(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (H7) min.	max.
—	—	24.987	25.000	31.967	31.992
				19	21

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471334
Diam. intérieur	25 mm
Diam. extérieur	32 mm
Épaisseur	12 mm
Poids	21 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE