

## Roulement à aiguilles MKM2516-JTEKT - MKM2516-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/mkm2516-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>2)</sup>	
$F_w$	$D$	$C$	$b$ min.	$C_r$	$C_{0r}$	Oil lub.		Caged type	With closed end
25	32	16	13.3	19.3	24.6	14 000		With open ends	MKM2516

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	31.967	31.992	26	30

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471365
Diam. intérieur	25 mm
Diam. intérieur	0.984" inch
Diam. extérieur	32 mm
Diam. extérieur	1.26" inch
Epaisseur	16 mm
Epaisseur	0.63" inch
Poids	30 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE