

Roulement à aiguilles BM2824-JTEKT - BM2824-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bm2824-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BHM

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|----------|-------------------------|----------|--------------------------------------|-------|---------------------------|-----------------|
| F_w | D | C | C_r | C_{10} | Oil lub. | | Caged type | |
| | | b min. | | | | | With open ends | With closed end |
| 28 | 34 | 24 | — | 29.0 | 76.7 | 4 600 | | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (F6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| BM2824 | | 27.987 | 28.000 | 33.967 | 33.992 | 42 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952471617 |
| Diam. intérieur | 28 mm |
| Diam. extérieur | 34 mm |
| Épaisseur | 24 mm |
| Poids | 42 g |
| Conditionnement | - |
| Norme | - |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE