

Roulement à aiguilles BHTM3015-JTEKT - BHTM3015-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bhtm3015-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|----|----|-------------------------|-----------------|--------------------------------------|--|---------------------------|-----------------|
| F _w | D | C | C _r | C _{0r} | Oil lub. | | Caged type | |
| | | | | | | | With open ends | With closed end |
| 30 | 40 | 15 | 16.6 | 22.3 | 12 000 | | BHTM3015 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 29.987 | 30.000 | 39.967 | 39.992 | 41 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250003202 |
| Diam. intérieur | 30 mm |
| Diam. extérieur | 40 mm |
| Épaisseur | 15 mm |
| Poids | 41 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE