

## Roulement à aiguilles 32BTM4025PL-JTEKT - 32BTM4025PL-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/32btm4025pl-jtekt>

Drawn cup needle roller bearings 



Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$C_0$	$C_{0e}$	Oil lub.	Caged type With open ends With closed end
32	40	25	27.6	50.8	11 000	32BTM4025PL

  

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (H6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	31.984	32.000	39.989 <sup>4)</sup>	40.014 <sup>4)</sup>	57	—

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952472058
Diam. intérieur	32 mm
Diam. extérieur	40 mm
Épaisseur	25 mm
Poids	57 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE