


Roulement à aiguilles BHTM3530-JTEKT - BHTM3530-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/bhtm3530-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|-------------------------|----------------|--------------------------------------|---------------------------|
| F _w | D | C | b min. | C _r | C _{0r} | Oil lub. |
| 35 | 45 | 30 | 27.3 | 39.4 | 71.0 | 10 000 |
| | | | | | | Caged type |
| | | | | | | With open ends |
| | | | | | | With closed end |
| | | | | | | BHTM3530 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 34.984 | 35.000 | 44.967 | 44.992 | 96 | 109 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250003240 |
| Diam. intérieur | 35 mm |
| Diam. intérieur | 1.378" inch |
| Diam. extérieur | 45 mm |
| Diam. extérieur | 1.772" inch |
| Epaisseur | 30 mm |
| Epaisseur | 1.181" inch |
| Poids | 96 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE