


Roulement à aiguilles BTM5015-JTEKT - BTM5015-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/btm5015-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------------|---------------------------|-----------------|
| F_w | D | C | b min. | C_r | C_{10} | Oil lub. | Caged type | |
| | | | | | | With open ends | | With closed end |
| 50 | 62 | 15 | — | 24.3 | 36.4 | 7 300 | BTM5015 | |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) | | Housing bore dia. (N7) | | With open ends | With closed end |
| | | min. | max. | min. | max. | | |
| — | — | 49.984 | 50.000 | 61.961 | 61.991 | 73 | — |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952472935 |
| Diam. intérieur | 50 mm |
| Diam. extérieur | 62 mm |
| Épaisseur | 15 mm |
| Poids | 73 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE