

Roulement à aiguilles MKM5030-JTEKT - MKM5030-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/mkm5030-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|
| F_w | D | C | b min. | C_r | C_{10} | Oil lub. | With open ends | With closed end |
| 50 | 62 | 30 | 27.3 | 52.8 | 98.5 | 7 300 | | MKM5030 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 49.984 | 50.000 | 61.961 | 61.991 | 153 | 173 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952472980 |
| Diam. intérieur | 50 mm |
| Diam. extérieur | 62 mm |
| Épaisseur | 30 mm |
| Poids | 173 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE