



Roulement à rouleaux NN3032K-JTEKT - NN3032K-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nn3032k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> _{min}	<i>F</i> ₀	<i>C</i> ₀	<i>C</i> ₁₀	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
160	240	60	2.1	—	218	398	655	2 400	2 800	NN3032K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d</i> _a		<i>D</i> _a		<i>r</i> _a		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		171	—	—	229	221	2	9.38	9.08

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952473260
Diam. intérieur	160 mm
Diam. extérieur	240 mm
Épaisseur	60 mm
Poids	9080 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE