


Roulement à rouleaux NN3044K-JTEKT - NN3044K-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nn3044k-jtekt>

Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F₀₂</i>	<i>E₀₂</i>	<i>C₀₂</i>	<i>C₀₇</i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
220	340	90	3	—	310	752	1 370	1 600	1 900	NN3044K	NN3044K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d_a</i>		<i>D_a</i>		<i>r_a</i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		233	—	—	327	313	2.5	29.3	28.4

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952473468
Diam. intérieur	220 mm
Diam. extérieur	340 mm
Épaisseur	90 mm
Poids	28400 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE