


Roulement à rouleaux NNU4956-JTEKT - NNU4956-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nnu4956-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r min.	F _w	E _w	C _r	C _{0r}	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
280	380	100	2.1	308	—	976	2 200	1 300	1 500		

Mounting dimensions (mm)		Cylindrical bore		Tapered bore		Mass (kg)	
d _a min.	d _a max.	D _a min.	D _a max.	r _a min.	r _a max.	Cylindrical bore	Tapered bore
291	305	316	369	—	2	33.1	31.6

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952473949
Diam. intérieur	280 mm
Diam. extérieur	380 mm
Épaisseur	100 mm
Poids	33100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE