


Roulement à aiguilles 20NQ3020-JTEKT - 20NQ3020-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/20nq3020-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|---------------------|---------------------|---------------------|-------------------------|-----------------|--|--------------------|-------------|
| F _w | d | D | B | C _r | C _{0r} | Oil lub. | Without inner ring | |
| 20 | — | 30 | 20 | — | 19.8 | 26.4 | 22 000 | 20NQ3020 |
| Mounting dimensions (mm) | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | |
| With inner ring | | | | Without inner ring | With inner ring | | | |
| | d _s min. | D _s max. | r _s max. | — | 0.048 | — | | |
| | — | — | — | 28 | 0.3 | — | | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952477459 |
| Diam. intérieur | 20 mm |
| Diam. extérieur | 30 mm |
| Épaisseur | 20 mm |
| Poids | 48 g |
| Conditionnement | 1 |

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE