


Roulement à aiguilles NQ22-16-JTEKT - NQ22-16-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nq22-16-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
22	—	30	16	—	12.7	20.2	21 000	NQ22/16
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d_a	D_a	r_a	Without inner ring	With inner ring		
		min.	max.	max.	—	—		
		—	28	0.3	0.032	—		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477510
Diam. intérieur	22 mm
Diam. extérieur	30 mm
Épaisseur	16 mm
Poids	32 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE