


## Roulement à aiguilles 16NQ2316-JTEKT - 16NQ2316-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/16nq2316-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>e</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
16	—	23	16	—	13.1	16.4	27 000	<b>16NQ2316</b>
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> max.	Without inner ring	With inner ring		
		—	20	0.5	0.016	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3616060465511
Diam. intérieur	16 mm
Diam. extérieur	23 mm
Épaisseur	16 mm
Poids	18 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE