


Roulement à aiguilles NQ16-12-JTEKT - NQ16-12-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nq16-12-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	
16	—	24	12	0.3	7.7	9.6	28 000	NQ16/12
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d ₁ min.	D ₁ max.	r ₁ max.	Without inner ring	With inner ring		
		—	22	0.3	0.019	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952477664
Diam. intérieur	16 mm
Diam. extérieur	24 mm
Épaisseur	12 mm
Poids	19 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE