

Roulement à aiguilles MTM2520M-JTEKT - MTM2520M-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/mtm2520m-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	C_r	C_{0r}	Oil lub.		Caged type	
			min.				With open ends	With closed end
4	32	20	19.1	32.5	14 000		MTM2520M	

Full complement type		Recommended dimensions (mm)				Refer. Mass (g)	
With open ends	With closed end	Shaft dia. (φG) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	31.967	31.992	33	—

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250025457
Diam. intérieur	25 mm
Diam. extérieur	32 mm
Epaisseur	20 mm
Vitesse limite	14000 rpm
Poids	33 g
Charge dynamique	19.1 kN
Charge statique	32.5 kN
Conditionnement	1
Norme	Sans norme

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE