


## Roulement à rouleaux 22NQ3225-JTEKT - 22NQ3225-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/22nq3225-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>W</sub> 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.		
22	—	32	25	—	22.4	31.7	20 000	<b>22NQ3225</b>
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d <sub>a</sub>	D <sub>a</sub>	r <sub>a</sub>	—	—			
	max.	max.	max.	—	0.063			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482286
Diam. intérieur	22 mm
Diam. extérieur	32 mm
Épaisseur	25 mm
Poids	63 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE