

Roulement à rouleaux NQ24-12-JTEKT - NQ24-12-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq24-12-jtekt>

Machined ring needle roller bearings ————— Koyo
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	
24	20	32	12	9.6	14.4	19 000	NQ24/12	
Mounting dimensions (mm)				(roller) Mass (kg)		(roller) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
d _a min.	D _a max.	r _a max.	0.3	0.025	0.038			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482293
Diam. intérieur	24 mm
Diam. extérieur	32 mm
Épaisseur	12 mm
Poids	25 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE