


## Roulement à rouleaux NQI20-12-JTEKT - NQI20-12-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nqi20-12-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 – 37 mm

With inner ring



F <sub>w</sub>	Boundary dimensions (mm)				r (mm)	Basic load ratings (kN)		Limiting speed <sup>1)</sup> (min <sup>-1</sup> ) Oil lub.	Bearing No. Without inner ring
	d	D	B	B <sub>1</sub>		C <sub>r</sub>	C <sub>10</sub>		
24	20	32	12	—	0.3	9.6	14.4	19 000	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
		With inner ring	d <sub>1</sub> min.	D <sub>1</sub> max.	r <sub>1</sub> max.	Without inner ring	With inner ring		
		NQI20/12	22	30	0.3	0.025	0.038		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482309
Diam. intérieur	20 mm
Diam. extérieur	32 mm
Épaisseur	12 mm
Poids	38 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE