


Roulement à rouleaux NQI20-16-JTEKT - NQI20-16-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nqi20-16-jtekt>

Machined ring needle roller bearings **Koyo**
F_W 29 – 37 mm
With inner ring



F _w	Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
	d	D	B	B ₁	r _{min}	C _r	C ₁₀	Oil lub.			
24	20	32	16	—	0.3	13.4	22.2	19 000		—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
		With inner ring			Without inner ring	With inner ring					
		d ₁ min.	D ₁ max.	r ₁ max.	0.035	0.052					
		NQI20/16			22	30	0.3				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482323
Diam. intérieur	20 mm
Diam. extérieur	32 mm
Épaisseur	16 mm
Poids	52 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE