


Roulement à rouleaux NA4904UU-JTEKT - NA4904UU-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na4904uu-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



F_w	Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring	
	d	D	B	B_1	r	C_r	C_{10}	Oil lub.	—		
25	20	37	17	18	0.3	16.4	18.2	8 000	—	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
		With inner ring	d_a min.	D_a max.	r_a max.	Without inner ring	With inner ring	—	IRM202518		
		NA4904UU	22	35	0.3	—	0.078				

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482392
Diam. intérieur	20 mm
Diam. extérieur	37 mm
Épaisseur	17 mm
Poids	78 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE