


Roulement à rouleaux NQ28-30-JTEKT - NQ28-30-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq28-30-jtekt>

Machined ring needle roller bearings ————— Koyo
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	Without inner ring	
28	—	37	30	—	29.1	54.1	16 000	NQ28/30	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d _s min.	D _s max.	r _s max.	0.083	—				
	—	35	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482521
Diam. intérieur	28 mm
Diam. intérieur	1.102" inch
Diam. extérieur	37 mm
Diam. extérieur	1.457" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Poids	83 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE