


Roulement à rouleaux RNA69-22-JTEKT - RNA69-22-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/rna69-22-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_w 29 – 37 mm
Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
28	22	39	30	36.8	53.1	16 000	RNA69/22	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _a min.	D _a max.	r _a max.	Without inner ring	With inner ring		
		24	37	0.3	0.100	0.154	IRM222830	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482569
Diam. intérieur	28 mm
Diam. extérieur	39 mm
Épaisseur	30 mm
Poids	100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE