


Roulement à rouleaux NQ30-30-JTEKT - NQ30-30-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq30-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
30	—	40	30	—	33.5	58.5	15 000	NQ30/30
Mounting dimensions (mm)				(roller) Mass (kg)		(roller) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d_a	D_a	r_a	—	—			
	max.	max.	max.	0.099	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482651
Diam. intérieur	30 mm
Diam. extérieur	40 mm
Épaisseur	30 mm
Poids	99 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE