


## Roulement à rouleaux NQI28-20-JTEKT - NQI28-20-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nqi28-20-jtekt>

Machined ring needle roller bearings Koyo  
F<sub>W</sub> 29 – 37 mm  
With inner ring



| Boundary dimensions (mm) |    |    |    |                | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |  | Bearing No.        |
|--------------------------|----|----|----|----------------|-------------------------|-----------------|--|--|--------------------|
| F <sub>w</sub>           | d  | D  | B  | B <sub>1</sub> | C <sub>r</sub>          | C <sub>0r</sub> | Oil lub.   |  | Without inner ring |
| 32                       | 28 | 42 | 20 | —              | 24.3                    | 39.4            | 14 000   |  | —                  |
| Mounting dimensions (mm) |    |    |    |                | (Refer.) Mass (kg)      |                 | (Refer.) Applicable inner ring No.                 |  |                    |
| With inner ring          |    |    |    |                | Without inner ring      | With inner ring |  |  |                    |
|                          |    |    |    |                | 0.070                   | 0.098           |  |  |                    |
|                          |    |    |    |                |                         |                 |  |  |                    |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952482781 |
| Diam. intérieur | 28 mm         |
| Diam. intérieur | 1.102" inch   |
| Diam. extérieur | 42 mm         |
| Diam. extérieur | 1.654" inch   |
| Epaisseur       | 20 mm         |
| Epaisseur       | 0.787" inch   |
| Poids           | 98 g          |
| Conditionnement | 1             |

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE