


Roulement à rouleaux NA49-28R-JTEKT - NA49-28R-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na49-28r-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm
With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	C _r	C _{10r}	Oil lub.	Grease lub.	Without inner ring	
32	28	45	17	—	25.0	33.8	14 000	—	—	
Mounting dimensions (mm)					(roller) Mass (kg)		(roller) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NA49/28R					30	43	0.3	0.075	0.099	IRM283217

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482828
Diam. intérieur	28 mm
Diam. extérieur	45 mm
Épaisseur	17 mm
Poids	99 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE