


## Roulement à aiguilles NQIS25-22-JTEKT - NQIS25-22-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-aiguilles/aiguilles/nqis25-22-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$B_1$	$C_r$	$C_{10}$	Oil lub.	Without inner ring		
32	25	47	22	—	31.2	41.4	14 000	—		
Mounting dimensions (mm)					( roller ) Mass (kg)		( roller ) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NQIS25/22					27	45	0.3	0.123	0.167	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482842
Diam. intérieur	25 mm
Diam. extérieur	47 mm
Épaisseur	22 mm
Poids	167 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE