


Roulement à rouleaux NA4906D-JTEKT - NA4906D-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na4906d-jtekt>

Machined ring needle roller bearings 
F_w 29 – 37 mm
With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	B ₁	C _r	C _{0r}	Oil lub.	Without inner ring	
35	30	47	17	17	20.0	31.5	13 000	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring		d _a max.	D _a max.	r _a max.	Without inner ring	With inner ring			
NA4906D		32	45	0.3	0.081	0.114	IRM303517D		

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482897
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	17 mm
Poids	114 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE