


## Roulement à rouleaux NA4907UU-JTEKT - NA4907UU-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/na4907uu-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>w</sub> 29 – 37 mm  
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>w</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
42	35	55	20	29.0	40.9	4 700	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
NA4907UU	d <sub>a</sub> max.	D <sub>a</sub> max.	r <sub>a</sub> max.	—	0.173	IRM354221		

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483108
Diam. intérieur	35 mm
Diam. extérieur	55 mm
Épaisseur	20 mm
Poids	173 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE