


Roulement à rouleaux NQ45-20-JTEKT - NQ45-20-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq45-20-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	
45	—	55	20	—	27.9	52.7	10 000	NQ45/20
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _i min.	D _i max.	r _i max.	Without inner ring	With inner ring		
		—	51	0.6	0.100	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483207
Diam. intérieur	45 mm
Diam. extérieur	55 mm
Épaisseur	20 mm
Poids	100 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE