


Roulement à rouleaux NQ45-30-JTEKT - NQ45-30-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq45-30-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F _w	d	D	B	B ₁	C _r	C _{0r}	Oil lub.		Without inner ring	
45	40	55	30	—	40.9	86.1	10 000		NQ45/30	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
	d _s min.	D _s max.	r _s max.	0.6	0.138	0.214				

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483214
Diam. intérieur	45 mm
Diam. intérieur	1.772" inch
Diam. extérieur	55 mm
Diam. extérieur	2.165" inch
Epaisseur	30 mm
Epaisseur	1.181" inch
Poids	138 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE