


Roulement à rouleaux NQI50-25-JTEKT - NQI50-25-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nqi50-25-jtekt>

Machined ring needle roller bearings Koyo
F_W 29 – 37 mm
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
55	50	68	25	47.4	90.4	8 900	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
NQI50/25				54	64	0.8	—	0.255

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483474
Diam. intérieur	60 mm
Diam. extérieur	68 mm
Épaisseur	25 mm
Poids	255 g
Conditionnement	1

contact@123roulement.com

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE