

## Roulement à rouleaux NQ60-25-JTEKT - NQ60-25-JTEKT

<https://www.123roulement.com/roulement-palier/roulement-rouleaux/rouleaux/nq60-25-jtekt>

Machined ring needle roller bearings  **Koyo**  
F<sub>W</sub> 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
F <sub>e</sub>	d	D	B	C <sub>r</sub>	C <sub>0r</sub>	Oil lub.	Without inner ring	
60	—	72	25	—	45.4	97.3	7 900	<b>NQ60/25</b>
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> max.	0.164	—			
	—	68	0.5					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483603
Diam. intérieur	60 mm
Diam. extérieur	72 mm
Épaisseur	25 mm
Poids	164 g
Conditionnement	1

[contact@123roulement.com](mailto:contact@123roulement.com)

03 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE